



DT-991 Series & 200 Series

991/200 Series Mini Digital Multimeters provide multifunction and lower price. Rugged pocket design is easy and safe to use with protective holster.

Safety Conformance

EN61010-1 CATIII 600V

Includes protective holster

10A fused protection



Specifications

Function	Max. Range	Basic Accuracy	DT-991/200	DT-992/201	DT-993/202	DT-202T	DT-204	DT-204T
Voltage DC	600V	$\pm(0.8\% \pm 2d)$	*	*	*	*	*	*
Voltage AC	600V	$\pm(1.2\% \pm 10d)$	*	*	*	*	*	*
Current DC	10A	$\pm(1.2\% \pm 2d)$	*	*	*	*	*	*
Current AC	10A	$\pm(1.8\% \pm 7d)$		*/-	*	*	*	*
Resistance	2000 Ω	$\pm(0.8\% \pm 2d)$	*	*				
	40M Ω	$\pm(0.8\% \pm 2d)$			*	*	*	*
Temperature	760°C/1400°F	$\pm(3.0\% \pm 3d)$		*	*	*	*	*
Duty Cycle	0.1%~99.9%	$\pm(1.2\% \pm 2d)$			*	*	*	*
Frequency	9.999MHz	$\pm(1.5\% \pm 4d)$			*	*	*	*
Capacitance	200uF	$\pm(2.5\% \pm 5d)$			*	*		
	40mF	$\pm(2.5\% \pm 5d)$					*	*
Diode Check	Open voltage 2.8Vdc; Test current 1mA		*	*	*	*	*	*
Continuity	Threshold 30 Ω		*	*	*	*	*	*
Bat. Test	9V(6mA); 1.5V(100mA)		*					

991 Series:

Size(HxWxD): 121.5mm x 60.6mm x 40mm

Weight: 150g

200 Series:

Size(HxWxD): 146mm x 66.2mm x 41.5mm

Weight: 200g

991 Series:

Accessories: Test leads, Holster and 9V battery, clamshell.

200 Series:

Accessories: Test leads, K-type temperature probe (201, 202, 202T, 204, 204T) and 9V battery, gift box.