



Accessories ● Standard Equipment

Casing 55 set
Model: DFR551
Part No. 191W94-5 ●

Casing 41 set
Model: DFR452
Part No. 191W93-7 ●



Model	Description	Part No.	Pcs/set
DFR551	PH 2 (+) 155mm ● (Include 3 pcs)	191V02-0	5
DFR452	PH 2 (+) 137mm ● (Include 3 pcs)	191V01-2	5

Flat Tape Collated Screws

50pcs screws/belt, 1,000pcs screws/box
Drywall Screws



Application	L (mm)	Shank Dia (mm)	Recess	Thread	Finish	Screws /Belt	Screws /Box	Screwdriver		Part No.
								DFR551	DFR452	
Drywall to metal stud (Plasterboard to metal stud)	25	3.9	PH2	Fine	Phosphated	50pcs	1000pcs	Yes	Yes	F-30913
	35	3.9	PH2	Fine	Phosphated	50pcs	1000pcs	Yes	Yes	F-31153
	45	3.9	PH2	Fine	Phosphated	50pcs	1000pcs	Yes	Yes	F-30939
Drywall to wood (Plasterboard to wood)	35	3.9	PH2	Coarse	Phosphated	50pcs	1000pcs	Yes	Yes	F-31179
	41	3.9	PH2	Coarse	Phosphated	50pcs	1000pcs	Yes	Yes	F-31182
	55	3.9	PH2	Coarse	Phosphated	50pcs	1000pcs	Yes	Yes	F-31140
Drywall to wood (Plasterboard to hard wood)	30	3.9	PH2	Hi-Low	Yellow Zinc (5 micron)	50pcs	1000pcs	Yes	Yes	F-32245
Fermacell Screws (Gypsum Fibreboard to hard wood)	30	3.9	PH2	Hi-Low	Phosphated	50pcs	1000pcs	Yes	Yes	F-31748
Decking Screws (Wood to wood)	55	4.2	PH2	Coarse, Part Thread	Stainless Steel	50pcs	1000pcs	Yes		F-32483
Wood Screws (Playwood to hard wood)	40	4.2	PH2	Hi-Low	Yellow Zinc	50pcs	1000pcs	Yes	Yes	F-31201
Wood Screws (Wood to wood)	50	4.2	SQ2	Coarse	Yellow Zinc	50pcs	800pcs	Yes		F-33218



Cordless Auto Feed Screwdriver DFR551 / DFR452

High rotation speed
6,000 rpm



Charging Time

Battery Model	Fast Charging		Standard Charging
	DC18RC	DC18RD	DC18SD
BL1815N 1.5Ah	15 min		30 min
BL1820B 2.0Ah	24 min		45 min
BL1830B 3.0Ah	22 min		60 min
BL1840B 4.0Ah	36 min		90 min
BL1850B 5.0Ah	45 min		110 min
BL1860B 6.0Ah	55 min		130 min

Cordless Auto Feed Screwdriver

DFR551Z / DFR452Z

	DFR551	DFR452
Variable Speed		
Screw Strip	3.5 - 4.2 x 20 - 41 mm	3.5 - 4.2 x 25 - 55 mm
Reversing		
Driving Shank (Hex)	6.35 mm (1/4")	6.35 mm (1/4")
No Load Speed (RPM)	0 - 6,000	0 - 6,000
Sound Pressure Level	74 dB(A)	75 dB(A)
Vibration Level	Screwdriving w/o Impact: 2.5 m/s ² or less	Screwdriving w/o Impact: 2.5 m/s ² or less
Dimensions (L x W x H)	w/o Battery: 396 x 88 x 165 mm w/ BL1830B / BL1840B / BL1850B / BL1860B: 396 x 88 x 211 mm	w/o Battery: 360 x 88 x 165 mm w/ BL1830B / BL1840B / BL1850B / BL1860B: 360 x 88 x 211 mm
Net weight	1.9 (BL1815N) - 2.2 kg (BL1860B)	1.9 (BL1815N) - 2.2 kg (BL1860B)

DFR551Z/DFR452Z: No battery, charger
Phụ kiện kèm theo: Hook (346317-0), casing 55 set (DFR551/191W94-5), casing 41 set (DFR452/191W93-7), + bit2-155 set/DFR551 (3 pcs), + bit2-137 set/DFR452 (3 pcs), + truss head screw M4X12 (266622-8)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

DFR551

55 mm (2-3/16")



DFR452

41 mm (1-5/8")



Continuous work amount

Model: DFR452
Battery: BL1850B / Trigger lock-on condition
Drove 25mm drywall screw through 12.5mm Drywall into 38mm SPF plate.

Push drive is on.
2,700 pcs



CÔNG TY TNHH MAKITA VIỆT NAM

Kho 556, Block 16, 191L-2 Đường số 3, KCN VSIP, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 382 8338 - Fax: 0274 382 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC
Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSIP Bắc Ninh, X. Phú Châu, TP. Từ Sơn, T. Bắc Ninh
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH ĐÀ NẴNG
102 Triều Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH CẦN THƠ
366 Vĩ Văn Kiệt, Khu Vực 5, P. An Thủy, Q. Bình Thủy, TP. Cần Thơ
ĐT: 0292 389 4358 Fax: 0292 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HẢI PHÒNG
Số 01 Lê Đức Thọ, Di An Hoàng Huy Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng
ĐT: 0225 863 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH NHÀ TRANG
Số 96 - 98 đường B6, Khu đô thị Việt Đỉnh Trung, Xã Vĩnh Ngọc, TP. Hòa Lạc, TP. Hà Nội
ĐT: 0246 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh
ĐT: 0283 821 5191



Collated drywall screw

Model	Diameter	Overall length
DFR551	3.5 - 4.2 mm	25 - 55 mm
DFR452		20 - 41 mm

**BL
MOTOR**



Push drive technology

The motor rotates at full speed only when the screw is pressed against the board to reduce power consumption and noise.



Motor starts up.



Tightening finished. Motor stops when bit is removed from screw head.



Continuous work amount

Model: DFR452
Battery: BL1850B / Trigger lock-on condition
Drove 25mm drywall screw through 12.5mm Drywall into 38mm SPF plate.

Push drive is on.

2,700 pcs

Push drive is off.

880 pcs

More reliable Casing attachment

Enhanced durability

- Screw feeding mechanism redesigned to improve durability and reduce screw fall
- Improved durability by changing the material of Casing from Plastic to Aluminum.



Quick attachment / removal

Reduces the trouble of reversing and replacing a bit



Unfastening operation

The tool allows you to change the direction of driver bit rotation with ease, either towards the right (clockwise) to tighten a screw or towards the left (counterclockwise) to loosen a screw.



photo: DFR551

XPT