



Cordless Screwdriver
DFS452

Satisfy Professional's Needs



Excellent performance as
powerful as AC model



Push Drive Technology

in lock-on mode, the motor starts only when the fastener is engaged for work environment and to save battery power.



High power delivered by Brushless motor



Compact design with an overall length of 254mm (10")

One-touch locator
allows for easy locator installation/removal with a single action.

Silent clutch

Battery fuel gauge

- The power remaining in the battery can be indicated in 3 stages simply by pushing a button:
- 3 lights on : more than 50% of full battery capacity
- 2 lights on : 20% to 50% of full battery capacity
- 1 light on : less than 20% of full battery capacity

Single LED job light with afterglow function

- convenient for operation in dark job sites
- keeps on illuminating about 12-13 seconds after trigger release.



Charger

DC18RC
DC18RA



Two Port Multi Fast Charger
DC18RD



Charging time (3.0Ah)

DC18SF

Charging time (3.0Ah)
1 to 2 batteries : 60minutes
3 to 4 batteries : 120minutes



DC18SD

Charging time (3.0Ah)
60minutes



DC18SE (Automotive)

Charging time (3.0Ah)
60minutes



Hook

Brushless motor

- Maintenance-free due to no brush
- Energy production is more efficient than brushed DC motor because of no friction loss caused by brushes, enabling to lower amperage for reduced heat production and increased work amount on a single full battery charge.

Best possible tool body for screwdriving

ergonomically designed to:

- minimize hand fatigue and pain even in long continuous operation.
- give maximum power thrust.
- allow for much smoother and easier trigger pull.
- provide comfortable grip and better control with enlarged non-slip elastomer.

Lock-on button for continuous screwdriving



Powered by 18V Li-ion batteries



BL1850: 18V 5.0Ah
BL1840: 18V 4.0Ah
BL1830: 18V 3.0Ah



BL1820: 18V 2.0Ah
BL1815N: 18V 1.5Ah

Push Drive Technology

in lock-on mode, the motor starts only when the fastener is engaged for work environment and to save battery power.

Cordless Screwdriver DFS452

- Variable Speed
- Reversing
- Built-in Job Light
- Carrying Case

Capacity	Drywall screw : 4mm
Driving shank (Hex)	6.35mm
No load speed (rpm)	0-4,000
Dimensions (L x W x H)	BL1850: 254x79x259mm BL1815: 254x79x242mm
Net weight	BL1850: 1.8kg BL1815: 1.6kg

DFS452RME: 2 pin 4.0Ah (BL1840B), sạc nhanh (DC18RC)
DFS452Z: Không kèm pin, sạc

Standard Equipment : + truss head screw M4X12 (266622-8), hook (346317-0), +bit 2-25 (784261-7)(2 pcs).

weight according to EPTA-Procedure 01/2003
Items of standard equipment and specifications may vary by country or area.

CÔNG TY TNHH MAKITA VIỆT NAM

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

Kho S. Số 1, Đường Số 6 KCN - BT - DV VSP Bắc Ninh, X. Phú Chấn, TP. Từ Sơn, T. Bắc Ninh.
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HÀ NỘI

65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội.
ĐT: 0243 202 2385

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH ĐÀ NẴNG

102 Triều Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng.
ĐT: 0236 352 5070 / 0236 352 5170 Fax: 0236 352 5470

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH CẦN THƠ

386 Võ Văn Kiệt, Khu Vực S. P. An Thới, Q. Bình Thủy, TP. Cần Thơ.
ĐT: 0292 389 4358 Fax: 0292 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH BUỒN MA THUỘT

89 Lê Đức Thọ, P. Thống Nhất, TP. Buôn Ma Thuột, T. Đắk Lắk.
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HẢI PHÒNG

Số 01 Lô OH-01, Dự án Hoàng Huy Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng.
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH NHA TRANG

Là 36 - 38 đường B6, Khu đô thị Vinh Diễm Trung, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HỒ CHÍ MINH

Số 12 Trịnh Văn Căn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh.
ĐT: 0283 821 5191