

pH/ORP

15 PC-502/OC-502

pH/ORP Monitor



■ Features

- Correctable to operation control value with measured value shifting function
- With holding function, and capable of output holding at maintenance time (by the non-voltage contact point input signal from outside)
- With hysteresis setting function, and averaging function

■ Optional Electrodes

	Model	Type	Temp Compensation	Liquid Junction	Cable Length
pH	GR-1	Liquid Filling Type	without	single	5m
	GR-11	Liquid Filling Type	attached	single	5m
	GR-1B	Liquid Filling Type	without	single	5m
	MK-1	Liquid Non-Filling Type	without	double	5m
ORP	MK-11	Liquid Non-Filling Type	attached	double	5m
	OR-1	Liquid Filling Type	without	single	5m
	MK-OR	Liquid Non-Filling Type	without	double	5m
	MK-ORF	Liquid Non-Filling Type (for In-line Type)	without	double	5m

■ Meter

Name of product	pH Monitor	ORP Monitor
Model	PC-502	OC-502
Display	LED 3. 1/2 Digits	
Measuring Range	0.00~14.00	-1900~+1900mV
Min. Resolution	0.01pH	1mV
Transmit output	DC4~20mA (initial setting) 0~14pH	DC4~20mA (initial setting) 0~±700mV
	With scaling function	
Contact output	High & Low each a, b contact	
Hold Function	Transmit output & contact output	
Shift Range of	Within ±2pH	Within ±100mV
Measured Value	(adjust value to operational Value)	
Power Supply	AC 85~240V 50/60Hz	

■ Optional Accessories (please specify at ordering)

Electrodes, PP Holder, Flow type holder, Connector box, Fixing tool, Brush cleaner, Jet cleaners.

■ pH/ORP Detector, Holder, Cleaner

