

Digital Clamp Meter



GCM-403



FEATURES

- * AC/DC 600A/600V Max Input
- * Auto Range, Auto Power Off
- * Capacitance Measurement
- * Frequency Measurement
- * Temperature Measurement
- * Max. Clamp Size : Ø 28mm

GCM-403

DIGITAL METERS

Digital Clamp Meter



GCM-407



FEATURES

- * True RMS Measurement
- * AC 600A/750V, DC 1000V Max Input
- * Auto Range, Auto Power Off
- * Capacitance Measurement
- * Non-Contact Voltage sensing function
- * Max. Clamp Size : Ø 30mm

GCM-407

DIGITAL METERS

SPECIFICATIONS	
ACV	
Range	4V, 40V, 400V, 600V
Resolution	0.001V, 0.01V, 0.1V, 1V
Accuracy	±(1.0 + 5) ~ ±(1.2 + 5)
Input Impedance	≥10MΩ // 100pF at least
Frequency Response	40~400Hz
ACA	
Range	40A, 600A
Resolution	0.01A, 0.1A
Accuracy	±(2.5 + 5) ~ ±(2.5 + 8)
Frequency Response	50~60Hz
DCV	
Range	400mV, 4V, 40V, 400V, 600V
Resolution	0.1mV, 0.001V, 0.01V, 0.1V, 1V
Accuracy	±(0.8 + 1) ~ ±(1.0 + 3)
Input Impedance	≥10MΩ
DCA	
Range	40A, 600A
Resolution	0.01A, 0.1A
Accuracy	±(2.0 + 5)
OHM	
Range	400Ω, 4kΩ, 40kΩ, 400kΩ, 4MΩ, 40MΩ
Resolution	0.1Ω, 0.001kΩ, 0.01kΩ, 0.1kΩ, 0.001MΩ, 0.01MΩ
Accuracy	±(1.0 + 2) ~ ±(1.5 + 2)
DIODE	
Range	4V
Resolution	0.001V
Open-circuit Voltage	Approx. 1.48V
CONTINUITY	
Range	400Ω
Resolution	0.1Ω
Accuracy	The buzzer turns on for resistance lower than 10Ω
Open-circuit Voltage	Approx. 0.45V
CAPACITANCE	
Range	40nF, 400nF, 4μF, 40μF, 100μF
Resolution	0.01nF, 0.1nF, 0.001μF, 0.01μF, 0.1μF
Accuracy	±(4.0 + 3) ~ ±(5.0 + 10)
FREQUENCY	
Range	10Hz, 100Hz, 1kHz, 10kHz, 100kHz, 1MHz, 10MHz
Resolution	0.001Hz, 0.01Hz, 0.1Hz, 1Hz, 10Hz, 100Hz, 1kHz
Accuracy	±(4.0 + 3) ~ ±(5.0 + 10)
TEMPERATURE (°C only)	
Range	-40°C ~ 1000°C
Accuracy	±(2.5 + 3) ~ ±(8.0 + 5)
OTHER FUNCTION	
Data Hold, REL	
LCD DISPLAY	Liquid crystal display : Displays 4000 counts maximum.
CLAMP OPENING DIAMETER	28mm Maximum
POWER SOURCE	9V battery (16F22)
DIMENSIONS & WEIGHT	210 (L) x 76 (W) x 30 (H) mm; Approx. 260g

ORDERING INFORMATION

GCM-403 Digital Clamp Meter

ACCESSORIES :
User manual x 1, Test leads, Temperature probe

The GCM-407 is digital clamp meter with true RMS measurement. Featuring tapered jaws, a wide range (AC 600A/750V, DC 1000V max input), capacitance measurement as well as non-contact voltage sensing function and the ability to keep MAX/MIN or hold data and automatically power down make the GCM-407 suitable for almost any cable measurement task.

SPECIFICATIONS	
ACV	
Range	6V, 60V, 600V, 750V
Resolution	0.001V, 0.01V, 0.1V, 1V
Accuracy	±(1.2 + 5) ~ ±(1.5 + 5)
Input Impedance	≥10MΩ
Frequency Response	40~400Hz
ACA	
Range	6A, 60A, 600A
Resolution	0.001A, 0.01A, 0.1A
Accuracy	±(2.5 + 5) ~ ±(2.5 + 30)
Frequency Response	50~60Hz
DCV	
Range	600mV, 6V, 60V, 600V, 1000V
Resolution	0.1mV, 0.001V, 0.01V, 0.1V, 1V
Accuracy	±(0.8 + 1) ~ ±(1.0 + 8)
Input Impedance	≥10MΩ
OHM	
Range	600Ω, 6kΩ, 60kΩ, 600kΩ, 6MΩ, 60MΩ
Resolution	0.1Ω, 0.001kΩ, 0.01kΩ, 0.1kΩ, 0.001MΩ, 0.01MΩ
Accuracy	±(1.0 + 2) ~ ±(1.5 + 5)
DIODE	
Range	6V
Resolution	0.001V
Open-circuit Voltage	Approx. 3.3V
CONTINUITY	
Range	600Ω
Resolution	0.1Ω
Accuracy	The buzzer turns on for resistance lower than 30Ω
Open-circuit Voltage	Approx. 1.2V
CAPACITANCE	
Range	99nF, 999nF, 9μF, 99μF, 999μF, 9mF, 59mF
Resolution	0.01nF, 0.1nF, 0.001μF, 0.01μF, 0.1μF, 0.001mF, 0.01mF
Accuracy	±(4.0 + 5) ~ ±10
NCV (Non-Contact Voltage)	
Range	< 10mm
Accuracy	AC Voltage only
OTHER FUNCTION	
Data Hold, MAX/MIN, REL, Backlight, Flashlight	
LCD DISPLAY	Liquid crystal display : Displays 6000 counts maximum.
CLAMP OPENING DIAMETER	30mm Maximum
POWER SOURCE	3 AAA 1.5V zinc manganese batteries
DIMENSIONS & WEIGHT	228 (L) x 77 (W) x 41 (H) mm; Approx. 265g (inclusive of the battery)

ORDERING INFORMATION

GCM-407 Digital Clamp Meter with True RMS Measurement

ACCESSORIES :
User manual x 1, Test leads, Carrying case