

4 Color Print Head Pad Printing Machine(GW-M4-ST)

Zoom



Model number: GW-M4-ST

Printing area: 60*170mm

Printing speed: 600PCS/hr

MOQ: 1 set

Payment terms: T/T,Western Union,Paypal,L/C

Package way: plywood

Delivery way: by sea

Lead time: within 20days



Enquiry



Back

Describe

Four-Color Sealed Ink Cup Pad Printer with Shuttle Table

Function introduction

1. PLC program, kinds of printing model option
2. Auto 4-digit counter built-in, and stat. Printing quantity
3. Locating by servo, it is no necessary to use mechanical to adjust
4. Adopting Japanese THK linear guide and ball screw to construct linearity terrace
5. Every printing head lift up or fall separately, it isn' t limited with outside dimension of products
6. Airframe adopts coin alloy, and metal coating surface
7. Worktable, printing head and ink tray can be adjusted X. Y. Z direction
8. Sucking ink and the pressure of printing pad can be adjusted independently
9. Scraper stroke can be adjusted
10. It has function of leveling ink by sliding automatically on front /back, this can avoid printing ink partial solidification
11. The speed of all the cylinders have an independent regulator intortum
12. Adopts original Japan SMC and Taiwan MINDMAN pneumatic component
13. Each adjustable location has scale logo
14. It has the function of forbidding the pad fallen when no air pressure enter into
15. The machine is running fast, it is steady and low voice

feature and parameter

Action model option Fully automatic semi-automatic manual self-programming

(You can choose to print 1, 2, 3, 4 color Arbitrary rotating to print

Working style Arbitrary positioning for 1-4 workstation

Start-up method Panel foot switches

Fixing method of shuttle and rotary table Pulse positioning

Driving method of shuttle and rotary table Servo motor

Scraper working style Electronic switch

Scraper pressure controller By pressure regulating Valve

Steel plate size 100*200mm

Printing speed 600PCS/hr

Power :220V 50-60Hz 2000W

Air pressure 5-7bar

Transverse distance 200MM

Vertical distance 75MM

Max. Printing area 60* 170MM

Centre distance of ink tray 170MM

Repeat precision < 0.05MM

Printing workstation 1 PC

Fixing clamp method Locking by mounting plate screw

Choosing the material of clamp Bakelite epoxide resin

Plastic fastness style By wooden bolt

Activate Wind