

Fume Hood (Dry Scrubber Built-in)LDF-N150LU

[Page Top](#)[Product Summary](#)[Specifications](#)[Same series products](#)

Fume Hood (Dry Scrubber Built-in)

LDF-N150LU

Item Code : A003017

Model : LDF-N150LU

[Page Top](#)[Product Summary](#)[Specifications](#)[Same series products](#)

Fume Hood (Dry Scrubber Built-in) (LDF-N150LU)

[Contact Us](#)[Printing](#)

Product Summary

Dry exhaust gas treatment system installed. It helps to remove organic solvents which difficult to remove, acids, alkali etc.

Features of Fume Hood (Dry Scrubber Built-in) (LDF-N150LU)

Adsorption device installed on top of fume hood.

Activated carbon and chemical adsorbent (4 type) are selectable.

Time meter that shows the time of adsorbent is equipped.

Specifications

Specifications

Item Code

A003017

Fume Hood (Dry Scrubber Built-in)LDF-N150LU

Page Top	Product Summary	Specifications	Same series products
Interior		Stainless SUS304 1mm	
Working surface (selection)		Stainless (L)	
Glass door		Tempered glass 6mm balance weight	
Water faucet		Single type 1pc	
Socket		AC115V/220V × 1pc	
Fluorescent lamp		32W 1pc	
Case material		SUS	
Adsorption		Adsorbent amount (K type) 30 k	
Timer		0 ～ 9,999.9h (for adsorbent specification time)	
Differential pressure		For pre-filter (0 ～ 490Pa / 0 ～ 50mmH2O) 1pc	
Safety mechanism		Exhaust delay timer, Door falling prevention stopper, Flow monitor	
Option		Gas tap, LED, safety mechanism	
Exhaust air volume		16m ³ /min	
Internal static pressure		245Pa (25mmH2O)	
External dimensions (W×D×H mm)		1500×750×2600mm	
Power Source		115/220V	
Weight		390kg	

Maintenance and warranty

- 1. Conditions: temperature and humidity: 23 deg.C+/-5 deg.C, 65%RH+/-20% (no load)
- 2. External dimensions do not include protrusions.

Same series products



Fume Hood (Dry Scrubber Built-in) (LDF-N180S)



Fume Hood (Dry Scrubber Built-in) (LDF-N180SU)



Fume Hood (Dry Scrubber Built-in) (LDF-N120L)

