

Product Summary

Features of Fume Hood (withExhaust volume controller for Air intake and Exhaust) (LDXA-N180S)

Specifications

Specifications

| A002975 |
|---|
| LDXA-N180S |
| d steel plate (chemical resistance baking finish) |
| stos and non-combustible decorative board (Baffle plate: multi slit system) |
| |

| Working surface materials | Ceramitite (S) |
|--|--|
| Glass window | Tempered glass 6mm Balance weight |
| Water faucet | Single type 1pc |
| Outlet | AC115/ 220V with dual grounding wire (dropout prevention) 1pc. |
| Fluorescent lamp | 40W 1set |
| Safety feature | Exhaust delay timer, Door falling prevention stopper, Emergency exhaust switch, Flow monitor |
| Atmosphere conditions | Room temp. : 5 to 35 oC, Room humidity : 20 to 80% (No condensation) |
| Option | Gas tap, LED, Safety mechanism |
| Standard discharge air quantity | 6 to 20 m3/min |
| Air intake volume | 6 to 20 m3/min |
| Static pressure | 108Pa (at 20 m3/min) |
| Air intake pressure | 157Pa (at 20 m3/min) |
| $\label{eq:external dimensions} \textbf{(WxDxH mm)}$ | 1800×750×2600mm |
| Power Source | AC115/220V |
| Weight | 430kg |

Same series products



Fume Hood (withExhaust volume controller for Air intake and Exhaust) (LDXA-N120S)



Fume Hood (withExhaust volume controller for Air intake and Exhaust) (LDXA-N150S)