

model AE-1152E DC Low Ohm METER

Optimum for the auto measurement of Ultra-low Resistor.

- Measurement not to be influenced by thermal electromotive force.
- Impressed the measuring current at pulse interval.
- Contact-check is equipped as standard function.
- Measuring range : $0.0000\text{m}\Omega \sim 1.5000\text{k}\Omega$
- Available to measure the percent the set reference value :
 $0.1\text{m}\Omega \sim 1\text{k}\Omega / \pm 50.00\%$ [Minimum resolution of $10\text{n}\Omega$]
- RS-232C, GP-IB and Centronics output available. [option]
- Comparison result by built-in comparator is open-collector output and displayed as LO, GO, HI by LED and buzzer.
- Measuring current/voltage-check are built-in as standard function.
- Available to shift output.



AEMIC CORPORATION,

Model AE-1152E DC Low Ohm METER

SPECIFICATIONS

Measuring range and Accuracy (at 23°C±5°C) :

Range	Measuring range	Resolution	Measuring current	Accuracy
1mΩ	0.0000mΩ ~ 1.5000mΩ	0.1μΩ	1A	within ±(0.01%rdg+1μΩ) ±3digits[Average] ±4digits[Slow] ±5digits[Fast]
10mΩ	0.000mΩ ~ 15.000mΩ	1μΩ		
100mΩ	0.00mΩ ~ 150.00mΩ	10μΩ	300mA	
1Ω	0.0000Ω ~ 1.5000Ω	100μΩ	100mA	
10Ω	0.000Ω ~ 15.000Ω	1mΩ		
100Ω	0.00Ω ~ 150.00Ω	10mΩ	10mA	
1kΩ	0.0000kΩ ~ 1.5000kΩ	100mΩ	1mA	
%	0.1mΩ~1.0000kΩ/±50.00%	0.01%[10nΩ]	Mentioned above	Refer to the instruction manual

Voltage at terminals open :	below 9V
Measuring method :	4-terminal measurement with contact check.
Measuring time :	【Free running mode】 2~10times/sec. 【Remote start mode】 about 9msec~400msec.
Comparator setting range :	mΩ test mode: 0~15000[both for the upper and lower limit] % test mode : 50.00%[low limit:0~-50.00%、 high limit:0~+50.00%]
Indication comparator's comparison result :	LO/GO/HI, LED display and buzzer.
Control signal :	input: START "L"[0V]→"H"[DC12V]⇒start HOLD open or "H"[DC12V]⇒freerun / "L"[0V]⇒hold output LO/GO/HI, CONT-E and EOC/ open collector[40V/100mA max.]
Operation condition :	【Temp.】 5°C~+40°C、【Humidity】 below 85%
Outer dimension :	333(W)×99(H)×300(D)mm 【excluding protruding parts such as rubber legs, etc.】
Weight :	about 3kg
Power supply :	AC85V~265V、 50~60Hz、 about 60VA
Option :	RS-232C Interface
[Only one kind of interface can be provided with the checker]	GP-IB Interface
	Printer output[8 bit parallel Centronics]

Option	● RS-232C	Only one kind of interface can be provided with the checker.
	● GP-IB	
	● Printer output[Centronics]	
	● Printer Cable	
	● Short termination(Zero ohm standard resistor)	

AEMIC CORPORATION,

34, Higashikoyanouchicho, Takeda, Fushimi-ku, Kyoto, 612-8448, Japan

TEL: 075-612-0710 FAX: 075-612-0750

E-Mail: sales@ae-mic.com

http://www.ae-mic.com